



A POLI-TAPE GROUP Company

# TEC MARK 5052

## Silver Frosty

### Product Information

Polymeric PVC Film (translucent, 80 µ) with clear solvent based acrylic adhesive (permanent), laminated on an one-sided claycoated silicone paper liner (120 g/m<sup>2</sup>).

The PVC offers an excellent dimensional stability.

Etched glass film for mid-to long-term window decoration. Coated with a solvent based pressure sensitive acrylic adhesive, enabling wet application.

Especially designed to create sand blasting and frosty effects when applied on glasses and mirrors. Additionally printable with solvent and eco-solvent based inkjet printers.

Designed to be highly resistant to solvent ink aggression during printing process and to guarantee very good printing performance on any solvent and eco-solvent based ink-jet printer.

Particularly suitable for application on flat, curved and slightly corrugated surfaces. No adhesive residue after removal, if correctly applied.

### Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

### Recommendations for laminating

Please ensure the print is perfectly dry before laminating. We suggest to let the material dry for at least 48 hours after printing.

### Technical Data

Carrier:	Polymeric PVC, highly stabilized, calendered
Thickness:	80 µ      +/- 5 %
Adhesive:	clear solvent acrylic, permanent
Adhesion:	5,5 N/cm
Liner:	one-sided clay-coated silicone paper (120 g/m <sup>2</sup> )
Application temperature:	+10 - +40 °C
Temperature durability :	- 40 - +80 °C
Outdoor durability:	5-7 years (unprinted film)

### Standard Dimensions

1220 mm x 50 m  
1370 mm x 50 m  
1550 mm x 50 m

### Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

#### KEMICA S.r.l.

Via F.lli Rusjan, 76 - Frazione Rupa  
34070 Savogna d'Isonzo (GO) - ITALIA

Phone: +39 0481 882 501  
Fax: +39 0481 882 440

E-Mail: [info@kemicasrl.it](mailto:info@kemicasrl.it)  
Internet: [www.kemica.it](http://www.kemica.it)

12/09/2016

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.