



UV INK LUS-190 CYAN

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 23-7-2020 Revision date: 12-12-2024 Supersedes version of: 6-7-2023 Version: 1.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : UV INK LUS-190 CYAN
UFI : 4C6N-R9VF-T602-N4KX
Product code : LUS19-C-BA
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use

Title	Use descriptors
UV INK LUS-190 CYAN	SU0, PC18, PROC1

Full text of use descriptors: see section 16

1.3. Details of the supplier of the safety data sheet

Mimaki Europe B.V.
Stammerdijk 7E
1112 AA Diemen
Netherlands
T +31 20 4627640
reach@mimakieurope.com

1.4. Emergency telephone number

Emergency number : National Poisons Information Centre +31 (0)30 - 274 8888
(Only for the purpose of informing medical personnel in cases of accidental intoxications.
The emergency phone number is 24 hours/day available.)

Country/Area	Organisation/Company	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Reproductive toxicity, Category 1B H360
Hazardous to the aquatic environment – Acute Hazard, Category 1 H400
Hazardous to the aquatic environment – Chronic Hazard, Category 2 H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

UV INK LUS-190 CYAN

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)	:	  
		GHS07 GHS08 GHS09
Signal word (CLP)	:	Danger
Contains	:	Hexamethylene diacrylate; 4-(1-oxo-2-propenyl)-morpholine; diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide
Hazard statements (CLP)	:	H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H360 - May damage fertility or the unborn child. H410 - Very toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	:	P201 - Obtain special instructions before use. P261 - Avoid breathing mist, vapours, spray. P264 - Wash hands, forearms and face thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P308+P313 - IF exposed or concerned: Get medical advice/attention. P391 - Collect spillage.
Extra phrases	:	Restricted to professional users.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (75980-60-8)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (75980-60-8)

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
Substance(s) not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (75980-60-8)

UV INK LUS-190 CYAN

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	% w/w (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hexamethylene diacrylate (Note D)	CAS-No.: 13048-33-4 EC-No.: 235-921-9 EC Index-No.: 607-109-00-8 REACH-no: 01-2119484737-22	≥ 75	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Aliphatic urethane acrylate	-	10 – 20	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319
diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide substance listed on REACH Candidate List	CAS-No.: 75980-60-8 EC-No.: 278-355-8 EC Index-No.: 015-203-00-X REACH-no: 01-2119972295-29	5 – 10	Skin Sens. 1B, H317 Repr. 1B, H360Fd
4-(1-oxo-2-propenyl)-morpholine	CAS-No.: 5117-12-4 EC-No.: 418-140-1 EC Index-No.: 613-222-00-3 REACH-no: 01-2120102080-83	0,1 – 1	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 2, H373

Note D: Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: If skin irritation or rash occurs: Get medical advice/attention. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May damage fertility or the unborn child.
Symptoms/effects after inhalation	: May cause an allergic skin reaction.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

UV INK LUS-190 CYAN

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 5: Firefighting measures

5.1. Extinguishing media

- | | |
|--------------------------------|--|
| Suitable extinguishing media | : Foam. Dry powder. Carbon dioxide. Water spray. Sand. |
| Unsuitable extinguishing media | : Do not use a heavy water stream. |

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

- | | |
|--------------------------------|---|
| Precautionary measures fire | : Eliminate all ignition sources if safe to do so. |
| Firefighting instructions | : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment. |
| Protection during firefighting | : Do not enter fire area without proper protective equipment, including respiratory protection. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- | | |
|------------------|--|
| General measures | : Provide local exhaust or general room ventilation to minimize dust and/or vapour concentrations. Exclude sources of ignition and ventilate the area. |
|------------------|--|

For non-emergency personnel

- | | |
|----------------------|-----------------------------------|
| Emergency procedures | : Evacuate unnecessary personnel. |
|----------------------|-----------------------------------|

For emergency responders

- | | |
|----------------------|--|
| Protective equipment | : Equip cleanup crew with proper protection. |
| Emergency procedures | : Ventilate area. |

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- | | |
|-------------------------|--|
| Methods for cleaning up | : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. |
| Other information | : Dispose of this material and its container at hazardous or special waste collection point. Non- sparking tools should be used. |

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- | | |
|-------------------------------|--|
| Precautions for safe handling | : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing mist, vapours, spray. Wear suitable protective clothing, gloves and eye or face protection. |
| Hygiene measures | : Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. |

7.2. Conditions for safe storage, including any incompatibilities

- | | |
|------------------------|---|
| Storage conditions | : Keep only in the original container in a cool well ventilated place. Keep container closed when not in use. |
| Incompatible products | : Oxidizing agent. Iron oxide. Strong bases. |
| Incompatible materials | : Sources of ignition. Direct sunlight. |

UV INK LUS-190 CYAN

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL and PNEC

Hexamethylene diacrylate (13048-33-4)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	2,77 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	24,48 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	2,08 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	7,24 mg/m ³
Long-term - systemic effects, dermal	1,66 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0,0015 mg/l
PNEC aqua (marine water)	0,00015 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0,0243 mg/kg dwt
PNEC sediment (marine water)	0,00243 mg/kg dwt
PNEC (Soil)	
PNEC soil	0,00397 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	2,7 mg/l
4-(1-oxo-2-propenyl)-morpholine (5117-12-4)	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	300 mg/kg bodyweight/day
Acute - systemic effects, inhalation	132,24 mg/m ³
Long-term - systemic effects, dermal	300 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	132,24 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0,012 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0,009428 mg/kg dwt
PNEC (Soil)	
PNEC soil	0,001442 mg/kg dwt

8.2. Exposure controls

Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure. Safety glasses. Gloves. Protective clothing.

UV INK LUS-190 CYAN

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Chemical goggles or safety glasses (acc. EN 166)

Skin protection

Skin and body protection:

Wear suitable protective clothing. Standard. EN 13034

Hand protection:

Wear suitable gloves resistant to chemical penetration. Breakthrough time (EN 374-3:2003): > 480 min (www.echa.europa.eu). Use barrier gloves. (0.062mm). Butyl rubber gloves (0.7 mm). Gloves must be replaced after each use and whenever signs of wear or perforation appear

Respiratory protection

Respiratory protection:

Provide adequate ventilation. In case of inadequate ventilation wear respiratory protection. Extra personal protection: A/P2 filter respirator for organic vapour and harmful dust. Standard. EN 14387

Environmental exposure controls

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Cyan.
Odour	: Ester.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Non flammable.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 100 °C (closed cup)
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Viscosity, dynamic	: 18 – 20 mPa·s @ 25°C
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

Other safety characteristics

VOC content : < 15 %

UV INK LUS-190 CYAN

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

On exposure to light. Polymerisation risk.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. UV sources.

10.5. Incompatible materials

Oxidizer. Iron oxide. Strong bases.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Hexamethylene diacrylate (13048-33-4)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	3650 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

4-(1-oxo-2-propenyl)-morpholine (5117-12-4)

LD50 oral rat	588 mg/kg bodyweight Animal: other:rat, Sprague-Dawley, Guideline: other:EG B.1 teil B /OECD 401, 95% CL: 527 - 701
LD50 oral	588 mg/kg bodyweight Animal: other:, Guideline: other:, 95% CL: 524 - 701
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	1 mg/l/4h

29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper (147-14-8)

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (75980-60-8)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity), Guideline: other:

UV INK LUS-190 CYAN

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Skin corrosion/irritation : Causes skin irritation.

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (75980-60-8)

pH	4 – 7
----	-------

Serious eye damage/irritation : Causes serious eye irritation.

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (75980-60-8)

pH	4 – 7
----	-------

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Additional information : Based on available data, the classification criteria are not met

Carcinogenicity : Not classified

Additional information : Based on available data, the classification criteria are not met

Reproductive toxicity : May damage fertility or the unborn child.

STOT-single exposure : Not classified

Additional information : Based on available data, the classification criteria are not met

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (75980-60-8)

LOAEL (oral, rat)	250 – 300 mg/kg bodyweight
-------------------	----------------------------

NOAEL (oral, rat)	50 – 100 mg/kg bodyweight/day
-------------------	-------------------------------

STOT-repeated exposure : Not classified

Additional information : Based on available data, the classification criteria are not met

Hexamethylene diacrylate (13048-33-4)

NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
----------------------------	---

NOAEL (dermal, rat/rabbit, 90 days)	20 – 200 mg/kg bodyweight/day
-------------------------------------	-------------------------------

4-(1-oxo-2-propenyl)-morpholine (5117-12-4)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper (147-14-8)

NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: other:Guideline for 28-Day Repeated Dose Toxicity Test in Mammalian Species (Chemical Substances Control Law of Japan)
----------------------------	--

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (75980-60-8)

NOAEL (subacute, oral, animal/male, 28 days)	50 mg/kg bodyweight NOAEL (oral, rat)
--	---------------------------------------

NOAEL (subacute, oral, animal/female, 28 days)	50 mg/kg bodyweight NOAEL (oral, rat)
--	---------------------------------------

Aspiration hazard : Not classified

Additional information : Based on available data, the classification criteria are not met

Hexamethylene diacrylate (13048-33-4)

Viscosity, kinematic	3,85 – 6,75 mm²/s
----------------------	-------------------

11.2. Information on other hazards

Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Very toxic to aquatic life.

UV INK LUS-190 CYAN

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

Hexamethylene diacrylate (13048-33-4)	
LC50 - Fish [1]	10 mg/l Test organisms (species): Leuciscus idus
EC50 - Crustacea [1]	2,6 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	1,5 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	2,33 mg/l Test organisms (species): other:
LOEC (chronic)	0,24 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0,14 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	72,3 µg/L (39 d)
NOEC chronic crustacea	140 µg/L (21 d)
4-(1-oxo-2-propenyl)-morpholine (5117-12-4)	
LC50 - Fish [1]	220 mg/l (4 d)
LC50 - Other aquatic organisms [1]	220 mg/l (72 h)
EC50 - Crustacea [1]	120 mg/l 48 h
EC50 - Crustacea [2]	230 mg/l 24 h
EC50 - Other aquatic organisms [1]	120 mg/l Test organisms (species): other aquatic arthropod:DM
EC50 72h - Algae [1]	> 120 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (acute)	120 mg/l 72 h
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper (147-14-8)	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
LC50 - Fish [2]	355,6 mg/l Test organisms (species): other:Oncorhynchus mykiss (formerly named: Salmo gairdneri)
EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): other:Daphnia magna Straus
EC50 - Crustacea [2]	> 500 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	> 500 mg/l Test organisms (species): other:
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
LOEC (chronic)	> 1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	1 mg/l
diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (75980-60-8)	
LC50 - Fish [1]	1,4 mg/l Test organisms (species): Cyprinus carpio
LC50 - Fish [2]	6,53 mg/l (48h)
EC50 - Crustacea [1]	3,53 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 2,01 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	3,829 mg/l Source: Ecological Structure Activity Relationships

UV INK LUS-190 CYAN

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.2. Persistence and degradability

UV INK LUS-190 CYAN	
Persistence and degradability	May cause long-term adverse effects in the environment.
Hexamethylene diacrylate (13048-33-4)	
Persistence and degradability	Rapidly degradable
Biodegradation	100 %
4-(1-oxo-2-propenyl)-morpholine (5117-12-4)	
Persistence and degradability	Rapidly degradable
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper (147-14-8)	
Persistence and degradability	Rapidly degradable
Aliphatic urethane acrylate	
Persistence and degradability	Rapidly degradable
diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (75980-60-8)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

UV INK LUS-190 CYAN	
Bioaccumulative potential	Not established.
Hexamethylene diacrylate (13048-33-4)	
Partition coefficient n-octanol/water (Log Pow)	2,81 @ 25 °C
4-(1-oxo-2-propenyl)-morpholine (5117-12-4)	
Partition coefficient n-octanol/water (Log Pow)	-0,46 @ 21°C
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper (147-14-8)	
Partition coefficient n-octanol/water (Log Pow)	-1 23 oC
diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (75980-60-8)	
Partition coefficient n-octanol/water (Log Pow)	3,1 – 3,87 @ 23 °C and pH 6.4

12.4. Mobility in soil

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (75980-60-8)	
Mobility in soil	784,8 Source: Quantitative Structure Activity Relation

12.5. Results of PBT and vPvB assessment

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (75980-60-8)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (75980-60-8)

12.6. Endocrine disrupting properties

No additional information available

UV INK LUS-190 CYAN

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.7. Other adverse effects

Additional information : Avoid release to the environment.



SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecological waste information	: Avoid release to the environment.
European List of Waste (LoW, EC 2000/532)	: 08 03 12* - waste ink containing dangerous substances
HP Code	: HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	Environmentally hazardous substance, liquid, n.o.s.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Transport document description				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hexamethylene diacrylate), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hexamethylene diacrylate), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Hexamethylene diacrylate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hexamethylene diacrylate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hexamethylene diacrylate), 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-A EmS-No. (Spillage): S-F	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes

UV INK LUS-190 CYAN

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5L
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90
Orange plates	: 
Tunnel restriction code (ADR)	: -
EAC code	: •3Z

Transport by sea

Special provisions (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
Stowage category (IMDG)	: A

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provisions (IATA)	: A97, A158, A197, A215
ERG code (IATA)	: 9L

Inland waterway transport

Classification code (ADN)	: M6
Special provisions (ADN)	: 274, 335, 375, 601
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP
Number of blue cones/lights (ADN)	: 0

UV INK LUS-190 CYAN

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Rail transport

Classification code (RID)	: M6
Special provisions (RID)	: 274, 335, 375, 601
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBV
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Special provisions for carriage - Loading, unloading and handling (RID)	: CW13, CW31
Colis express (express parcels) (RID)	: CE8
Hazard identification number (RID)	: 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	UV INK LUS-190 CYAN ; Hexamethylene diacrylate ; 4-(1-oxo-2-propenyl)- morpholine	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	UV INK LUS-190 CYAN ; Hexamethylene diacrylate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains substance(s) listed on the REACH Candidate List in concentrations $\geq 0.1\%$ or SCL: diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (EC 278-355-8, CAS 75980-60-8)

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

VOC Directive (2004/42)

VOC content : < 15 %

UV INK LUS-190 CYAN

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

For the following substances of this mixture a chemical safety assessment has been carried out:

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

SECTION 16: Other information

Indication of changes		
Section	Changed item	Comments
	Revision date	Modified
	Supersedes	Modified
15		Added

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
STP	Sewage treatment plant

UV INK LUS-190 CYAN

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

TLM	Median Tolerance Limit
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

Data sources	: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Other information	: DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness.

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H360	May damage fertility or the unborn child.
H360Fd	May damage fertility. Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
Repr. 1B	Reproductive toxicity, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2

Full text of use descriptors

PC18	Ink and Toners
PROC1	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
SU0	Other

UV INK LUS-190 CYAN

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Repr. 1B	H360	Calculation method
Aquatic Acute 1	H400	Calculation method
Aquatic Chronic 2	H411	Calculation method

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.