
CAD-CUT[®] PS POLY-TWILL™

Available under the name of CAD-CUT[®] PS-Poly Twill, is our 100% Polyester twill on a clear plastic carrier. The special adhesive allows easy positioning of the twill onto fabric, without having to apply undue pressure before final application. The material is excellent for plotter cutting because of the clear carrier. CAD-CUT[®] PS-Poly Twill fabric is available in several colours.

CAUTION:

To prevent fraying of the fabric during washing, the edges must be sealed either by overprinting with other CAD-CUT[®] materials or by sewing



390

AVAILABLE IN

42 cm x ca. 22,8 m rolls

RECOMMENDED FABRICS

- 100% Cotton
- Poly/Cotton blend
- 100% Polyester
- Moven Nylon

CUTTING NOTES

You should always test cut prior to any production run. Remember cutter settings will need to be adjusted as the blade ages. For optimal cutting and weeding, maintain a line thickness of at least 2.0 mm for lettering and logos.

APPLICATION INSTRUCTIONS

- Temperature: 165° C
- Time: 10 sec.
- Pressure: light
- (#2-3 on Hotronix®)

MULTI-COLOR DESIGNS

Apply background for 3-5 seconds, peel carrier cold. Repeat for additional colors. Finish with final application of 18-20 seconds. Peel cold.

ACCESSORIES RECOMMENDED

- Grip Cover Sheet
- Cover Sheet Non-Sticky
- EZ Weeder[®]

CARE INSTRUCTIONS

Machine wash up to 40° C using mild detergent. Do not use bleach. Dry at normal dryer settings on household machines. Do not dry clean. Can be directly ironed.

STORAGE

Store in cool, dry area. Avoid direct heat, sunlight and humidity.

DETAILS









CAD-CUT[®] PS POLY-TWILL™



