

EASY LITE LAM & SOUND

HEAT-ASSISTED TOP ROLLER LAMINATOR WITH BOSE® SPEAKER

Professional heat-assisted top roller laminator for self-adhesive materials. It allows to laminate and mount.
Designed to be reliable and easy-to-use for perfect and high quality results.

- > Affordable and easy-to-use laminator complete with motorized two unwinding shafts, two rewinding shafts

NEW

User-friendly control panel with new roller pressure indicator: best results guaranteed avoiding "overpressure" when mounting and laminating (typical "smile" effect)

NEW

New motorized lifting of the upper roller for an effortless and faster lamination available

- > Equipped with integrated Bose SoundLink® Mini Bluetooth® speaker (it can be easily removed) connectable to any Bluetooth® devices to listen to your favorite music when laminating
- > It mounts images on panels, applies double-sided adhesive films, application tape and protective films
- > Ideal for the small and medium sized user
- > Load and unload of rolls of materials in seconds
- > User-friendly control panel

SUITABLE FOR:

- ✓ Rigid and flexible indoor displays
- ✓ Floor graphics
- ✓ Backlit displays
- ✓ Pop-up & trade shows graphics
- ✓ Roll-up banners
- ✓ Board mounts
- ✓ Outdoor signs
- ✓ Car wrapping
- ✓ Many more..





New motorized lifting of the upper roller (optional)



New roller pressure display




Mini Sound Link Bose® speaker Bluetooth®



Four aluminum shafts with millimeter scale with automatic locking system



Swing-up steel feed table for quick set-up



Front tray for prints



Photosensitive cells with automatic self-control of safety devices and emergency buttons

Rewinding shaft for adjusting the tension of the material

Unwinding shaft for adjusting the tension of the material


Unwinding shaft for printed media in rolls

Rear rewinding shaft



Rear table with cutting unit

Feeding control by hand (control panel) or foot pedal (hand free operation)



Feed-in guide

Working width	1600 mm (63 in)
Max. space between rollers	30 mm (1.2 in)
Coated rubber rollers	Ø 116 mm (4.6 in)
Heated upper roll preset	30°, 40°, 50° C (86°, 104°, 122° F)
Max. speed	5 m/min (16 ft./min)
Working height	900 mm (35 in)
Power supply	230 V - 50 Hz - 2500 W
Dimensions (W x D x H)	2000 x 650 x 1500 mm (79 x 26 x 59 in)
Weight	215 kg (474 lbs)
Packing Dimensions (W x D x H)	2150 x 850 x 1700 mm (85 x 33 x 67 in)
Packing Weight	260 kg (573 lbs)


Manufactured in compliance with CE regulations



Follow us:



Distributor



100% Made by FLEXA



100% Made in Italy

